

Series 9000 Column Cover Specifications

Section 05586 Architectural Metal Column Covers

Job Name:

SPECIFICATION

Part 1 - General

1.01 Description of work

A. Furnish all material necessary for a complete installation of the SERIES 9000 column covers. Column covers to be self-aligning, positive interlock, without exposed fasteners or supports.

1.02 Submittals

A. Submit complete shop drawings detailing quantities, sizes, finish, configurations, and column attachment methods.

B. Submit product literature, specifications, information, and installation instructions.

1.03 Quality Assurance

A. Manufacturer to have a minimum of ten years experience in the manufacturing of column covers.

B. Manufacturer to inspect all aspects of the product to ensure that specifications have been met, and that they comply with approved shop drawings.

C. Manufacturer shall issue a one year limited warranty ensuring product against defects in workmanship and materials.

Part 2 - Products

2.01 Acceptable Manufacturers:

Pittcon Industries

6409 Rhode Island Ave.
Riverdale, MD 20737

Pittcon Industries

3330 W. Flower Street
Phoenix, Arizona 85017

2.02 Materials

A. Column covers shall be roll-formed from .090" aluminum and clad with 28ga Ceramicsteel by Alliance to match architects sample.

B. All fasteners are to be concealed.

C. All support structures to be supplied by column cover manufacturer.

D. All column covers are to be shipped with protective material on all exposed surfaces.

2.03 Fabrication

A. Column covers shall be roll-formed to specific dimensions and tolerances, and accurately formed to radii shown on drawings.

B. Column covers shall be fabricated in two vertically divided sections attached with a demountable interlock joint.

C. Column covers shall be fabricated in single length heights of 16' where required, with the addition of stacking joints to allow for heights above 16'.

Part 3 - Execution

3.01 Inspection & Installation

A. Contractor to inspect column covers upon receipt to ensure that no damage has occurred during shipment.

B. Column cover to be correctly oriented and installed in accordance with manufacturer's shop drawings and installation instructions to ensure proper installation.

C. Column cover to be erected plumb and level.

3.02 Cleaning & Protection

A. Contractor to remove protective material supplied by column cover manufacturer.

B. Contractor to clean all visible surfaces after installation.

C. Contractor to protect column covers from damage by other trades.

Pittcon Industries Division Pittcon Custom Corporation

6409 Rhode Island Avenue
Riverdale, Maryland 20737

(800) 637-7638 , (301) 927-1000
Fax: (301) 699-8690

3330 W. Flower Street
Phoenix, Arizona 85043

(800) 637-7638 , (602) 233-9100
Fax: (602) 233-9400

Fabricated with Pride in



Riverdale, Maryland-U.S.A.

CC-9

Series 1500 Column Cover Specifications

Section 05586 Architectural Metal Column Covers

SPECIFICATION

Part 1 - General

1.01 Description of work

A. Furnish all material necessary for a complete installation of the SERIES 1500 column covers. Column covers to be self-aligning, positive interlock, without exposed fasteners or supports.

1.02 Submittals

A. Submit complete shop drawings detailing quantities, sizes, finish, configurations, and column attachment methods.

B. Submit product literature, specifications, information, and installation instructions.

1.03 Quality Assurance

A. Manufacturer to have a minimum of ten years experience in the manufacturing of column covers.

B. Manufacturer to inspect all aspects of the product to ensure that specifications have been met, and that they comply with approved shop drawings.

C. Manufacturer shall issue a one year limited warranty ensuring product against defects in workmanship and materials.

Part 2 - Products

2.01 Acceptable Manufacturers:

Pittcon Industries

6409 Rhode Island Ave.

Riverdale, MD 20737

Pittcon Industries

3330 W. Flower Street

Phoenix, Arizona 85017

2.02 Materials

A. Column covers shall be roll-formed from (*Specified Material*) with (*Specified Finish*) to match architects sample.

B. All fasteners are to be concealed.

C. All support structures to be supplied by column cover manufacturer.

D. All column covers are to be shipped with protective material on all exposed surfaces.

2.03 Fabrication

A. Column covers shall be roll-formed to specific dimensions and tolerances, and accurately formed to radii shown on drawings.

B. Column covers shall be fabricated in two vertically divided sections attached with a demountable interlock joint.

C. Column covers shall be fabricated in single length heights of 16' where required, with the addition of stacking joints to allow for heights above 16'.

Part 3 - Execution

3.01 Inspection & Installation

A. Contractor to inspect column covers upon receipt to ensure that no damage has occurred during shipment.

B. Column cover to be correctly oriented and installed in accordance with manufacturer's shop drawings and installation instructions to ensure proper installation.

C. Column cover to be erected plumb and level.

3.02 Cleaning & Protection

A. Contractor to remove protective material supplied by column cover manufacturer.

B. Contractor to clean all visible surfaces after installation.

C. Contractor to protect column covers from damage by other trades.

Pittcon Industries Division Pittcon Custom Corporation

6409 Rhode Island Avenue

Riverdale, Maryland 20737

(800) 637-7638 , (301) 927-1000

Fax: (301) 699-8690

3330 W. Flower Street

Phoenix, Arizona 85043

(800) 637-7638 , (602) 233-9100

Fax: (602) 233-9400

Fabricated with Pride in



Riverdale, Maryland-U.S.A.

CC-10

Series 100 Column Cover Specifications

Section 05586 Architectural Metal Column Covers

Job Name:

SPECIFICATION

Part 1 - General

1.01 Description of work

A. Furnish all material necessary for a complete installation of the SERIES 100 column covers, exclusive of field applied material (i.e. joint compound, etc.). Column covers to be monolithic with field finished seamless joints, without exposed fasteners or supports.

1.02 Submittals

A. Submit product literature, specifications, information, and installation instructions.

B. Submit complete shop drawings detailing quantities, sizes, configurations, and column attachment methods.

1.03 Quality Assurance

A. Manufacturer to have a minimum of ten years experience in the manufacturing of column covers.

B. Manufacturer to inspect all aspects of the product to ensure that specifications have been met, and that they comply with approved shop drawings.

C. Manufacturer shall issue a one year limited warranty ensuring product against defects in workmanship and materials.

Part 2 - Products

2.01 Acceptable Manufacturers:

Pittcon Industries

6409 Rhode Island Ave.
Riverdale, MD 20737

Pittcon Industries

3330 W. Flower Street
Phoenix, Arizona 85017

2.02 Materials

A. Column covers shall be roll-formed from .090" aluminum with factory primed finish and fabricated in two vertically divided sections attached with screws and with field finished joint.

B. All fasteners are to be concealed.

C. All support structures to be supplied by column cover manufacturer.

D. Column cover sections shall be supplied free of scratches and surface blemishes.

2.03 Fabrication

A. Column covers shall be roll-formed to specific dimensions and tolerances, and accurately formed to radii shown on drawings.

B. Column covers shall be fabricated in two vertically divided sections attached with a field taping joint.

C. Column covers shall be fabricated in single length heights of 16' where required, with the addition of stacking joints to allow for heights above 16'.

Part 3 - Execution

3.01 Inspection & Installation

A. Contractor to inspect column covers upon receipt to ensure that no damage has occurred during shipment.

B. Column cover to be correctly oriented and installed in accordance with manufacturer's shop drawings and installation instructions to ensure proper installation.

C. Column cover to be erected plumb and level.

3.02 Cleaning & Protection

A. Contractor to clean all visible surfaces after installation.

B. Contractor to protect column covers from damage by other trades.

Pittcon Industries Division Pittcon Custom Corporation

6409 Rhode Island Avenue
Riverdale, Maryland 20737

(800) 637-7638 , (301) 927-1000

Fax: (301) 699-8690

3330 W. Flower Street
Phoenix, Arizona 85043

(800) 637-7638 , (602) 233-9100

Fax: (602) 233-9400

Fabricated with Pride in



Riverdale, Maryland-U.S.A.

Series 2000 Column Cover Specifications

Section 05586 Architectural Metal Column Covers

Job Name:
SPECIFICATION

Part 1 - General

1.01 Description of work

A. Furnish all material necessary for a complete installation of the SERIES 2000 column covers. Column covers to be self-aligning, positive interlock column cover system without exposed fasteners or supports.

1.02 Submittals

A. Submit product literature, specifications, information, and installation instructions.

B. Submit complete shop drawings detailing quantities, sizes, configurations, and column attachment methods.

1.03 Quality Assurance

A. Manufacturer to have a minimum of ten years experience in the manufacturing of column covers.

B. Manufacturer to inspect all aspects of the product to ensure that specifications have been met, and that they comply with approved shop drawings.

C. Manufacturer shall issue a one year limited warranty ensuring product against defects in workmanship and materials.

Part 2 - Products

2.01 Acceptable Manufacturers:

Pittcon Industries

6409 Rhode Island Ave.
Riverdale, MD 20737

Pittcon Industries

3330 W. Flower Street
Phoenix, Arizona 85017

2.02 Materials

A. Column covers shall be extruded aluminum of .115" to .145" thickness with (*specified finish*) and fabricated in two vertically divided sections attached with demountable interlock assembly.

B. All fasteners are to be concealed.

C. All support structures to be supplied by column cover manufacturer.

D. Column cover sections shall be supplied free of scratches and surface blemishes.

2.03 Fabrication

A. Column covers shall be manufactured to specific dimensions and tolerances, and accurately formed to radii shown on drawings.

B. Column covers shall be fabricated in two vertically divided sections attached with a demountable interlock joint.

C. Column covers shall be fabricated in single length heights of 12' where required, with the addition of stacking joints to allow for heights above 12'.

Part 3 - Execution

3.01 Inspection & Installation

A. Contractor to inspect column covers upon receipt to ensure that no damage has occurred during shipment.

B. Column cover to be correctly oriented and installed in accordance with manufacturer's shop drawings and installation instructions to ensure proper installation.

C. Column cover to be erected plumb and level.

3.02 Cleaning & Protection

A. Contractor to clean all visible surfaces after installation.

B. Contractor to protect column covers from damage by other trades.

Pittcon Industries Division Pittcon Custom Corporation

6409 Rhode Island Avenue
Riverdale, Maryland 20737

(800) 637-7638 , (301) 927-1000

Fax: (301) 699-8690

3330 W. Flower Street
Phoenix, Arizona 85043

(800) 637-7638 , (602) 233-9100

Fax: (602) 233-9400



Series ECC Column Cover Specifications

Section 05586 Architectural Metal Column Covers

SAMPLE SPECIFICATION

Section 05600 Architectural Metal Column Covers

Part 1 - General

1.01 Description of work

A. Furnish all material necessary for a complete installation of the SERIES ECC column covers, exclusive of field applied material (i.e. joint compound, substructure, etc.).

1.02 Submittals

A. Submit complete shop drawings detailing quantities, sizes, finish, configurations, and column attachment methods.

B. Submit product literature, specifications, information, and installation instructions.

1.03 Quality Assurance

A. Manufacturer to have a minimum of ten years experience in the manufacturing of column covers.

B. Manufacturer to inspect all aspects of the product to ensure that specifications have been met, and that they comply with approved shop drawings.

C. Manufacturer shall issue a one year limited warranty ensuring product against defects in workmanship and materials.

Part 2 - Products

2.01 Acceptable Manufacturers

Pittcon Industries

6409 Rhode Island Ave.

Riverdale, MD 20737

Pittcon Industries

3330 W. Flower Street

Phoenix, Arizona 85017

2.02 Materials

A. Column covers shall be roll-formed from (*specified material*) with (*specified finish*) to match architects sample.

B. All fasteners are to be concealed.

C. All column covers are to be shipped with protective material on all exposed surfaces.

2.03 Fabrication

A. Column covers shall be roll-formed to specific dimensions and tolerances, and accurately formed to radii shown on drawings.

B. Column covers shall be fabricated in two vertically divided sections with attachment provided through bent-back installation fins.

Part 3 - Execution

3.01 Inspection & Installation

A. Contractor to inspect column covers upon receipt to ensure that no damage has occurred during shipment.

B. Column cover to be correctly oriented and installed in accordance with manufacturer's shop drawings and installation instructions to ensure proper installation.

C. Column cover to be erected plumb and level.

3.02 Cleaning & Protection

A. Contractor to remove protective material supplied by column cover manufacturer.

B. Contractor to clean all visible surfaces after installation.

C. Contractor to protect column covers from damage by other trades

Pittcon Industries Division Pittcon Custom Corporation

6409 Rhode Island Avenue

Riverdale, Maryland 20737

(800) 637-7638 , (301) 927-1000

Fax: (301) 699-8690

3330 W. Flower Street

Phoenix, Arizona 85043

(800) 637-7638 , (602) 233-9100

Fax: (602) 233-9400

Fabricated with Pride in



Riverdale, Maryland-U.S.A.

CC-12